

O Drum handlers

- Self powered attachments
- Lifting devices and booms
- Wide load handling

Recycling containers

- Premises cleaning
- Fall prevention cages

Truck forks

INVESTOR IN PEOPLE INVESTOR IN PEOPLE Understand Un

® 🕺

Contact Attachments Mochdre Industrial Estate Newtown Powys SY16 4LE

tel: 01686 611200 fax: 01686 611201

Sideways Drum Rotator Fork Mounted

Designed to facilitate controlled and effortless pouring of the contents of either steel or 'L' Ring plastic drums.

<u>Use :-</u>




Designed for controlled manual rotation of 210 litre drums, the attachment slides simply onto the truck forks. The gearbox allows controlled pouring and rotation through a full 360 degrees. Variations of girdle type are available to suit either steel or plastic drums. There is also a model available to suit smaller 110 litre drums.

| Model Reference | Capacity | No. of Drums | DrumTypes | Type of Operation | A' Load Centre | B Fork Spread | C Pocket Length |
|-----------------|----------|--------------|-----------|-------------------|----------------|---------------|-----------------|
| SDR-1-SC | 360 Kg | 1 | 1 | Orank Handle | 1360 mm | 685 mm | 1000 mm |
| SDR-2-SC | 360 Kg | 1 | 1 | Loop Chain | 1360 mm | 685 mm | 1000 mm |
| SDR-1-DS | 360 Kg | 1 | 1, 2 | Orank Handle | 1360 mm | 685 mm | 1000 mm |
| SDR-2-DS | 360 Kg | 1 | 1, 2 | Loop Chain | 1360 mm | 685 mm | 1000 mm |
| | | | | | | | |

Max Fork Size 140 x 50


| Model Reference | C of G | Weight |
|-----------------|--------|--------|
| SDR-1-SC | 695 mm | 112Kg |
| SDR-2-SC | 695 mm | 118Kg |
| SDR-1-DS | 695 mm | 112Kg |
| SDR-2-DS | 695 mm | 118Kg |




Ordering Information :-

Truck Capacity? Fork width and thickness? Max fork spread? Drum type? Drum weight? Drum Diameter?

Operation :-







In order to pick up the drum for transportation or pouring, set the girdle to the horizontal position by using the handle or chain fitted to the geared Turning Unit/gear box. The truck forks must then be positioned at a height such that the girdle fits around the centre of the drum, between the rolling hoops. Ensure that the drum is held securely before lifting. Once lifted into the pouring position, the drum is rotated by means of the handle or continuous loop chain. The worm gear locks the drum at any desired angle.

www.forklift-attachments.co.uk email : sales@forklift-attachments.co.uk

